



commercial Air Curtain



The air curtain adopts cross flow blower to generate high speed air flow downward, that be installed upward side of the entrance door or window, to isolate the indoor air from the outdoor air and reduce the loss of indoor cool air, also prevent the insects and dust from entering the indoor environment.



Washable filter



Quiet function



Compact design



Easier maintainability

- Optimized cross-flow fan and good performance motor are adopted.
- Micro processor controlling with high reliability and long service life.
- Anti-corrosion thanks to two-side painted electro-galvanized metal case.
- High quality galvanized steel casing with double-sided plastic spray processing, high anti-corrosion.
- Good strength structure provides powerful airflow.
- Integrated electric components, easy maintenance.
- High performance cross flow fan blade with 3D-optimized streamlined.
- Remote controlled operation.



Model	Air Curtain		FM-1.25-9-K	FM-1.25-12-K
Power Supply		Ph,V,Hz	220-230/50	220-230/50
Power Input			110	140
Air flow volume		m3/h	1200	1650
Sound Pressure Level (H/L)		dB(A)	59	61
Dimension (WxDxH)	Outline	mm	900x220x220	1200x220x220
	Package	mm	1015x270x256	1315x270x256
Net Weight/Gross Weight		kg	16/18	20/22
Loading Quantity	20'GP	sets	848	600
	40'GP/40'HQ	sets	954	746
Setting height		m	2.3~3	2.3~3
Standard	Wired remote controller		ZY611	ZY611

0.9mts- €265 €215

2 years parts and labour (excluding remote)

1.2mts- €295 €255

Price quoted above is supply only & inclusive of 18% VAT.

+356 2395 6000 sales@btmalta.com

BT Commercial LTD, The Watercourse, Mdina Road,
Zone 2, Central Business District, Birkirkara CDB2010, Malta

btmalta.com

Vat No: MT1554-7011

LIFE
WORTH
LIVING.