



BOSCH Climate 3000i

Self-cleaning mode	i-clean mode	Dry mode	Follow me mode	Wind Avoid me mode	WiFi	Gear mode	Eco mode
Silent mode	Anti-corrosion	8°C heating mode	Low ambient cooling mode	Auto restart	On/off timer	Weekly timer	

Efficient

The Climate 3000i is a versatile reversible air conditioning unit that delivers both heating and cooling from a single source. With an ErP rating of A++ for cooling and A+ for heating, it ensures optimal comfort for you with minimal energy consumption.

Peace and Quiet

Climate 3000i's silent function reduces the sound level of the indoor and outdoor unit to give you and your neighbours a good night's sleep.

Breathe in Clean Air

The 'i-clean' function eliminates up to 99% of bacteria. Also the double filtration system eliminates odours, harmful gases and volatile organic compounds in the air.

5 YEARS
WARRANTY

BOSCH ChillFest Cool Combos ❄️ Solo Specials

BUY
2 BOSCH CLIMATE 3000i



OR

GET
1 **BOSCH**
CLIMATE 3000i
12BTU **FREE**

25%
OFF


TECHNICAL SPECIFICATIONS

			CLIMATE3000i12	CLIMATE3000i18	CLIMATE3000i24
COOLING CAPACITY (MIN - NOM - MAX)		kW	1.3 - 3.5 - 4.3	3.4 - 5.3 - 5.9	3.4 - 7.0 - 8.2
COOLING CAPACITY (MAX)		BTU/h	14700	20130	28000
HEATING CAPACITY (MIN - NOM - MAX)		kW	1.1 - 3.8 - 4.4	1.5 - 5.6 - 5.8	3.1 - 7.3 - 8.2
HEATING CAPACITY (MAX)		BTU/h	14950	19960	28000
PDESIGNC		kW	3.6	5.3	7
EER/COP		W/W	3.19/3.70	3.42/3.20	2.91/3.43
SEER/SCOP		-	7.0/5.5	7.0/5.1	6.4/5.1
ENERGY CLASS			A++/A+++	A++/A+++	A++/A+++
AIR FLOW VOLUME (HI/MI/LO)		m ³ /h	530/400/350	800/600/500	1090/770/610
POWER SUPPLY		V/Ph/Hz	220-240V, 1PH, 50Hz	220-240V, 1PH, 50Hz	220-240V, 1PH, 50Hz
POWER INPUT	COOLING	W	1096	1550	2402
	HEATING	W	1027	1750	2130
CURRENT INPUT	COOLING	A	4.76	6.7	10.5
	HEATING	A	4.46	7.6	9.3
RATED CURRENT	COOLING	A	10	13	19
MAX. DISTANCE	LENGTH	m	25	30	50
	HEIGHT	m	10	20	25
OUTDOOR UNIT			CL3000IU 3.5 E	CL3000IU 5.3	CL3000I 7.0 E
NET DIMENSIONS(W x H x D)		mm	720x270x495	874x330x554	955x342x673
NET/GROSS WEIGHT		Kg	23.7/25.5	33.5/36.1	43.9/46.9
SOUND PRESSURE LEVEL/SOUND POWER LEVEL		dB(A)	55/62	57/65	60/67
ADDITIONAL GAS CHARGE		q/m	12	12	24
REFRIGERANT TYPE			R32	R32	R32
REFRIGERANT CHARGE		kg	0.65	1.1	1.45
LIQUID PIPE DIAMETER/GAS PIPE DIAMETER		mm (inch)	Φ6.35mm(1/4in)/Φ9.52mm(3/8in)	Φ6.35(1/4in)/Φ12.7(1/2in)	Φ9.52(3/8in)/Φ15.9(5/8in)
MAX. PIPE LENGTH WITHOUT ADDITIONAL CHARGE		m	5	5	5
OPERATION RANGE FOR COOLING/HEATING		°C	-15 ~ 50/-15 ~ 24	-15 ~ 50/-15 ~ 24	-15 ~ 50/-15 ~ 24
INDOOR UNIT			CL3000IU W 3.5 E	CL3000IU W 5.3	CL3000IU W 7.0
REFRIGERANT TYPE			R32	R32	R32
NET DIMENSIONS(W x H x D)		mm	802x200x295	971x228x321	1082x234x337
NET/GROSS WEIGHT		Kg	8.7/11.5	11.2/14.6	13.6/17.3
SOUND PRESSURE LEVEL (HI/MI/LO)		dB(A)	37/32/22	41/37/31	46/37/34.5
SOUND POWER LEVEL		dB(A)	56	56	62

*Bosch reserves the right to modify the specifications without prior notice, please confirm the final specifications with sales representatives.

CLIMATE3000i12:
€895 **€795**

CLIMATE3000i18:
€1,295 **€1,195**

CLIMATE3000i24:
€1,595 **€1,495**

**+2 YEARS
EXTENDED
WARRANTY**

To UPGRADE WARRANTY from 5 years to 7 years, visit our website (www.btmalta.com), or purchase directly from our showroom within 3 months of warranty start date.

Cost for upgarde : 9K BTU – 16K BTU €60 and 18K BTU – 24K BTU €120